









57 - TERMINAL & GROUNDING SCREWS



Usage: Captive screws for electrical contactors, relays, distribution strips, bus-bars, and grounding applications.



CATEGORY	57 Terminal Screws
MATERIAL	Screw: C1018, SS304 Clamp: C1055, SS304
FINISH	Steel: Zinc Trichromate Stainless Steel: None




Screw Size	Length	Part Number	Clamp Plate	Clamp Type	a	b	c	Wire Single	Solid Copper Double	Torque lb-in	100pk Wght	
M3-0.5	7	11-11124	11-11124	3	7.50	6.80	2.40				.27	11-11124
	7	X 57-1448	175-07	3	6.70	6.60	2.30	14-22	18-22			N/A
	8	171-8	171-8	3	6.0	6.90	2.45				.22	171-8
	6.5	405-6.5	405-6.5	N/A	7.15	5.15	2.05				.20	405-6.5
	8	412-8	412-8	N/A			1.05				.22	412-8
	8	716-8	716-8	2	7.75	7.75	1.70				.30	716-8
	6.5	57-1623		3?							.20	162300
M3.5-0.6	8	57-1440	110-8	1	7.61	7.61	1.77	12-22	12-22		.26	144000
	5.5	129-5.5	129-5.5	N/A							.20	129-5.5
	9.3	519-9.3	519-9.3	3	7.40	7.70	2.88				.34	519-9.3
	9	205-09B	205-09B	3	7.15	7.60	2.60				.30	205-09B
	9.3	180-9.3	180-9.3	3	7.60	7.80	2.95				.32	180-9.3
	9.5	57-1620	281-9.5pz	3	7.65	8.00	3.35	12-22	12-22		.34	162000
	8	57-1621	221-08	3	7.60	7.00	2.60	12-22	12-22		.28	162100
	9	X 57-1441	110-9	1	7.61	7.61	1.77	12-22	12-22			N/A
	9.5	57-1452	180-9	3	7.60	7.90	2.90	12-22	12-22		.32	145200
	9	57-1455	205-09	3	7.10	8.00	2.60	12-22	12-22		.31	145500
	9.5	57-1459	255-09	3	7.60	7.90	2.90	12-22	12-22			N/A
	9.5	57-1622	173-9a	1	7.61	7.61	1.77	12-22	12-22		.27	571622
	12	281-12pz	281-12pz	3	8.40	9.20	3.75				.49	281-12PZ
	7.5	X 57-1460	256-07	3	7.10	7.70	2.40	12-22	12-22			N/A
	7.6	X 57-1446	174-07	3	7.10	8.65	2.60	12-22	12-22			N/A

57-2.0-Termilock


All Dimensions subject to change without notice. Dimensions are for reference only.

www.eisennet.com







57 - TERMINAL & GROUNDING SCREWS



Usage: Captive screws for electrical contactors, relays, distribution strips, bus-bars, and grounding applications.



CATEGORY	57 Terminal Screws
MATERIAL	Screw: C1018, SS304 Clamp: C1055, SS304
FINISH	Steel: Zinc Trichromate Stainless Steel: None




Screw Size	Length	Part Number	Clamp Plate	Clamp Type	a	b	c	Wire Single	Solid Copper Double	Torque lb-in	100pk Wght
	9.5	X 57-1447	174-09	3	7.10	8.65	2.60	12-22	12-22		N/A
M4-0.7	8	164-8	164-8	3	9.80	9.75	3.35			.46	
	10	164-10	164-10	3	9.95	9.60	3.30			.54	
	10	602-10	602-10	4	Min 7.90 Max 8.10	7.90 8.10	1.60			.44	
	11	710-11	710-11	N/A	9.95	9.95	1.90			.56	
	13.5	282-13.5pz	282-13.5pz	3	9.65	9.85	3.75			.58	
	14	188-14	188-14	3	9.65	9.50	3.75			.55	
	15.5	282-15.5pz	282-15.5pz	3	11.65	9.90	4.05			.71	
	15.5	282-D25	282-D25	3	9.65	9.80	3.90			.61	
	11	517-11	517-11	3	9.60	9.60	3.85			.51	
	13	57-1624	443-13	3						.65	
	11	57-1453	188-11	3	9.80	9.70	3.70	10-22	14-22	.51	
	14	X 57-1458	254-14	3	10.40	10.20	4.70	10-22	14-22		N/A
	11	57-1444	112-11	2	10.57	10.57	2.09	10-22	14-22	.48	
	10	57-1454	189-10	4	9.70	9.70	2.00	10-22	14-22	.44	
	11	X 57-1449	176-11	4	9.70	9.70	2.00	10-22	14-22		N/A
	12	505900	Stainless Steel	5	10.5	15.5	7.5	20	20	.83	
M5	12	238-12	238-12	3	13.0	11.0	3.35			.84	
	15	249-15c	249-15c	3	12.80	10.85	3.90			.97	
M5-0.8	13	57-1456	209-13	3	12.70	14.15	4.30	8-22	14-22	only 5pcs in stock!	
	16	X 57-1457	209-16	3	12.70	14.15	4.30	8-22	14-22		N/A
	14	X 57-1451	177-14	3	11.70	14.20	4.30	8-22	14-22		N/A

57-2.0-Termilock


All Dimensions subject to change without notice. Dimensions are for reference only.

www.eisennet.com







57 - TERMINAL & GROUNDING SCREWS



Usage: Captive screws for electrical contactors, relays, distribution strips, bus-bars, and grounding applications.



CATEGORY	57 Terminal Screws
MATERIAL	Screw: C1018, SS304 Clamp: C1055, SS304
FINISH	Steel: Zinc Trichromate Stainless Steel: None



Screw Size	Length	Part Number	Clamp Plate	Clamp Type	a	b	c	Wire Solid Copper Single	Wire Solid Copper Double	Torque lb-in	100pk Wght
6-32	5/16	57-1442	110-5/16	1	7.61	7.61	1.77	12-22	12-22		.27
	3/8	X 57-1443	110-3/8	1	7.61	7.61	1.77	12-22	12-22		N/A
8-32	3/8	57-1609	112-3/8	2	10.57	10.57	2.09	10-22	14-22		.59
		57-1609ss		2	10.45	10.45	1.80				.51
	7/16	57-1445	112-7/16	2	10.57	10.57	2.09	10-22	14-22		.60
10-32	7/16	805066		2	13.35	13.35	2.05				.75
N/A	N/A	00046	N/A	N/A							1.15

